OIL SANDWICH ADAPTER
INSTRUCTION SHEET
Part #'s: 1313, 1320, 1322, 1350, 1358 & 1327

BEFORE INSTALLING THIS TRANS-DAPT OIL SANDWICH ADAPTER, MEASURE CLEARANCE BEHIND THE FACTORY FILTER. ALLOW FOR THICKNESS OF THE ADAPTER PLUS 3/4" FOR FILTER REMOVAL.

1. Remove factory oil filter from engine.

2. Install sandwich adapter on factory filter landing with the appropriate O-ring installed in the adapter.

3. Screw sleeve nut on factory filter nipple until snug.

4. Position adapter in direction desired; tighten with wrench to about 25 foot pounds of torque.

5. Install oil cooler (not included) as per manufacturer's instructions.

6. Reinstall factory oil filter.

   CAUTION:
   1. *If filter O-ring is flush with rim of filter, rim may hit adapter first, not allowing a good seal. This may occur with Japanese brands. Select another brand.*
   2. *DO NOT OVERTIGHTEN cooler lines when connecting to the sandwich adapter.*

12438 Putnam Street • Whittier, CA 90602 • tel (562) 921-0404 • fax (562) 921-7515

oil-sandwich-adapter-instructions.cdr